

# Package: fftw (via r-universe)

October 21, 2024

**Version** 1.0-9

**Title** Fast FFT and DCT Based on the FFTW Library

**Description** Provides a simple and efficient wrapper around the fastest Fourier transform in the west (FFTW) library  
<http://www.fftw.org/>.

**Depends** R (>= 3.0.0)

**SystemRequirements** fftw3 (>= 3.1.2)

**License** GPL-2

**RoxygenNote** 6.0.1

**NeedsCompilation** yes

**Author** Olaf Mersmann [aut], Sebastian Krey [ctb], Uwe Ligges [ctb, cre]

**Maintainer** Uwe Ligges <ligges@statistik.tu-dortmund.de>

**Date/Publication** 2024-09-20 16:00:02 UTC

**Repository** <https://uligges.r-universe.dev>

**RemoteUrl** <https://github.com/cran/fftw>

**RemoteRef** HEAD

**RemoteSha** 1c69d8f41b707e7b074e38d502f52d9873e52b73

## Contents

FFT . . . . .	2
planFFT . . . . .	3

## Index

4

**FFT***Calculate (inverse) DFT using the FFT method***Description**

see title

**Usage**

```
FFT(x, ..., plan, inverse=FALSE)
IFFT(x, ..., plan, scale=TRUE)
DCT(x, ..., plan, type=1, inverse=FALSE)
IDCT(x, ..., plan, type=1, scale=TRUE)
```

**Arguments**

x	(complex) vector to process
...	ignored
plan	FFTW plan, can be missing
inverse	perform inverse transform, provided for fft compatibility.
scale	scale results
type	type of DCT

**Author(s)**

Olaf Mersmann &lt;olafm@statistik.uni-dortmund.de&gt;

**See Also**[planFFT](#)**Examples**

```
n <- 2**16
x <- rnorm(n)
p <- planFFT(n)
y <- FFT(x, plan=p)

Mod(x - IFFT(FFT(x)))
```

---

**planFFT***Create FFTW plan*

---

**Description**

see title

**Usage**

```
planFFT(n, effort=0)
planDCT(n, type=1, effort=0)
```

**Arguments**

n	size of transform
type	type of DCT
effort	how hard fftw tries to find an optimal plan (0 to 3)

**Author(s)**

Olaf Mersmann <olafm@statistik.uni-dortmund.de>

**See Also**

[FFT](#) and [IFFT](#)

# Index

DCT (FFT), [2](#)

FFT, [2](#), [3](#)

IDCT (FFT), [2](#)

IFFT, [3](#)

IFFT (FFT), [2](#)

planDCT (planFFT), [3](#)

planFFT, [2](#), [3](#)